Functions	Series 505				
Locking screw	(a)				
Thumb roller	(4)				

Specifications

Accuracy	Refer to the list of specifications				
Delivered	In a case				

Optional accessories

No.	Description
050083-10	75 base for depth measurement for models up to 200
050084-10	100 base for depth measurement for models up to 200
050085-10	125 base for depth measurement for 300 models



Titanium coating

Dial Caliper

Series 505

This dial caliper offers you the following benefits:

• A titanium coating is applied to the sliding surfaces to give you enhanced durability (except for 0-300mm model).





505-671



505-673

Metric										
No.	Range [mm]	Graduation	Accuracy	Sliding titanium coated	L [mm]	a [mm]	b [mm]	c [mm]	d [mm]	Mass [g]
505-680	0-100	0,01 mm. 1 mm/rev	±0,015 mm	•	180	40	21	16,5	16	151
505-671	0-150	0,02 mm. 2 mm/rev	±0,03 mm	•	231	40	21	16,5	16	175
505-681	0-150	0,01 mm. 1 mm/rev	±0,02 mm	•	231	40	21	16,5	16	176
505-672	0-200	0,02 mm. 2 mm/rev	±0,03 mm	•	288	50	24,5	20	16	185
505-682	0-200	0,01 mm. 1 mm/rev	±0,03 mm	•	288	50	24,5	20	16	186
505-673	0-300	0,02 mm. 2 mm/rev	±0,04 mm		403	64	27,5	22	20	370





