Functions	Series 573
ORIGIN (ABS-Zero)	(a)
Auto Power OFF	(4)
after 20 min. non use	
Low voltage alarm	(a)
Data output	(4)

Specifications

Accuracy	Refer to the list of specifications (excluding quantizing error)
Max. response speed	Unlimited
Digital step	0,01 mm
Battery life	aprox. 15000 hours
Display	LCD, Character Height 7,5 mm
Delivered	In a case, including 1 battery
Delivered	in a case, including 1 battery


Optional accessories

No.	Description
05CZA624	Digimatic cable with data switch (1 m)
05CZA625	Digimatic cable with data switch (2 m)
02AZD790A	Connecting cable U-Wave with data switch
06ADV380A	USB Input Tool Direct cable (2 m)

Consumable spares

No.	Description
938882	Battery SR44





ABSOLUTE Digimatic Neck Caliper

Series 573

These neck calipers enable measurements in hard to reach places. They offer you the following benefits:

• You can measure wall thickness inside bores and recesses.







573-651




573-654 Point jaw type

Metric				
No.	Range [mm]	Accuracy	Thumb roller	Mass [g]
573-651	0-150	±0,03 mm	(4)	157
573-653	0-150	±0,03 mm		157

Metric		Point jaw type			
	No.	Range [mm]	Accuracy	Thumb roller	Mass [g]
	573-652	0-150	±0,03 mm	(4)	157
	573-654	0-150	±0,03 mm		157





Point jaw type

