

Colour fastness to Crocking (or rubbing) is a standard that even the most simple of quality expectations will require.



The Roaches Crocktec is designed to allow everybody (with the correct consumables) to be able to perform this testing procedure.

Advanced materials allow almost frictionless movement at the crank pin and arm guide frame, whilst allowing totally lubricant-free operation.

## **FORM**

Crocktec has a perfectly designed specimen clamp to allow many different sample types to be tested without the need for specialist fittings.

A simple spring clip securely fits the crocking cloth to the rubbing "finger"


## **FUNCTION**

- Crocktec is fitted with a stroke counter as standard
- The standard 9N loading weight is easily changed for other loading variations.
- Crocktec build quality allows for accurate stroke length each and every time











## **TECHNICAL SPECIFICATIONS DIMENSIONS**

Crocktec (Manual)

LENGTH: 620mm DEPTH: 100mm

HEIGHT: 270mm (with handle up)

**UNIT WEIGHT:** 3kg

**Motorised Crocktec** 

LENGTH: 650mm DEPTH: 200mm 220mm HEIGHT: **UNIT WEIGHT:** 10kg



## **STANDARDS**

AATCC

M&S

> M&S C08

> AATCC 8

> AATCC 165

BS

NFXT

> BS FN ISO 105 - X12

>TM06



Roaches machines meet specifications set by leading retailers such as:













