

ICI SNAG MACE TESTER



STANDARDS

ASTM D3939

JIS L1058

The ICI SNAG MACE TESTER has been developed to determine the snagging resistance of heavy duty fabrics.

This tester can conform to but is not limited to the standards above.

For more standards conformance please email sales@roaches.co.uk or call +44 (0)1924 420083

The apparatus is supplied with 4 rotating cylinders which are fitted with felt sleeves and covered with the test fabric. The number of rotations are controlled by a pre-set electronic counter.

Roaches reserve the right to alter the specifications or modify the appearance of products without prior notice.



Unit Features

- Rotating cycle number can be pre-set and displayed on the digital counter.
- Automatically stops when pre-set cycle has been reached.
- Adjustable chain length.
- Rubber lined holders for safe storage of test mace balls.
- Pre-Installed felt sleeves manufactured to ASTM D3939 as standard.

Key Specifications

Power Supply	220V, 50-60Hz, 60W
Counter Range	1-9999
Working Positions	4
Speed	60 rpm \pm 2 rpm
Test Area	\varnothing 82mm x 210mm Width
Mace Ball	Weight 160g \pm 10g
Mace Tips	11 Tips, 10mm long, Ends \varnothing 0.13mm
Chain Working Width	125mm, \varnothing 10mm
Size	900 x 500 x 450mm
Weight	50kg

Optional Extras

- Pack of 12 - Tungsten Carbide Points (Code: 6000-0897)
- Pack of 4 - ASTM D3939 Felt Sleeves (Code: 6000-0955)
- Pack of 10 - Retaining Rings for Cylinders (Code: 6000-0956)
- ASTM D3939 Photographic Standards Grade 1-5 (Code: 5000-0004)

Roaches reserve the right to alter the specifications or modify the appearance of products without prior notice.